

# FALL DAMPER FDP

The fall damper is used for filling. The produce falls from chute to chute to reduce fall damage. When the sensor detects the produce, the machine retracts the chutes.



### **General description**

The fall damper is used for filling. The produce falls from chute to chute to reduce fall damage. When the sensor detects the produce, the machine retracts the chutes.

On demand, the machine can be available in painted mild steel or in stainless steel. The bearings and drive/idle rollers are made of mild steel. We have models available in 60 and 80 cm widths.



All dimensions in cm

		FDP 60	FDP 80
А	Width of machine	60	80

All capacities are indications based on experience from the past and depend on the agro climatic, soil and logistic conditions of the product, Allround VP does not guarantee any of these.

### Characteristics

- Models are available in 60 and 80 cm widths. 1
- Produce falls from chute to chute to reduce fall damage ~
- ✓ A sensor detects the produce, the machine retracts the chutes
- On demand, the machine can be available in painted mild steel or in stainless steel ✓

## **Options:**

#### Material and treatment (frame)

	Painted mild steel	Frame is made from painted mild steel. The bearings and drive/idle rollers are from mild steel		
	Stainless steel	Frame is made from stainless steel. The bearings and drive/idle rollers are from mild steel		
Ele	ctrical control			
	No electric	Motors and necessary sensors only. Wiring, sensors and/or control panel are not included		
	Stand-alone	Motors, necessary sensors, switch box and control box		
	Central control in line	Motors and necessary sensors		
Mat	Material and treatment (electrical panel)			


Painted mild steel	The electrical panel is made from painted mild steel

Stainless steel The electrical panel is made from stainless steel





**FDP 60** 











	615	
865		

For discussion only! The dimensions are approximately. We are free to resize and change the machines, when we deem it necessary.

Tol principle: ISO 8015	General tolerances: ISO 2		10768 F	Fit system: ISO 286 Geometrical tolerancing:		ng: ISO 1101		
6 7	Project: Fall damper automatic							
$\Psi \Box$	Des	Description: FDP 60						
	Surf	Surface:						
	Eng	ineer:	JAJ	Scale:	1:15	001520	20	Revision:
ALLROUND	Dat	e:	27-1-2022	Sheet size:	: A3	100152036		00
www.altoundvp.nl				Unit:	mm	Sheet: 1 of 1		••